

PLASTIC STEEL PUTTY (A)

PRODUCT INFORMATION

	<u>Stock No.</u> 10112 10115	<u>Package Size</u> 500g 1kg
Description	The original metal filled and machinable epoxy putty for economical, dependable maintenance and repair work.	
Recommended Applications	<ul style="list-style-type: none"> Repairs cracks and breaks in equipment, machinery or castings Patches and rebuilds blow holes or pits in castings Rebuilds worn equipment, pumps and valve bodies Restores bearing journals and races 	

PRODUCT DATA

Typical Physical Properties	Colour	Grey		
	Mix Ratio by Volume	2.5:1		
	Mix Ratio by Weight	9:1		
	% Solids by Volume	100		
	Pot life at 25°C/ mins	45		
	Specific Volume CC/Kg	429		
	Cured Shrinkage cm/cm	0.0006		
	Specific Gravity	2.33		
	Temperature resistance / °C	Dry 121°C		
	Coverage	858cm ² /Kg @ 5mm		
	Cured Hardness / Shore D	85 D		
	Dielectric Strength KV/mm	1.18		
	Adhesive Tensile Shear / MPa	19		
	Compressive Strength MPa	57		
	Coefficient of Thermal Expansion x10 ⁻⁶ cm/cm/°C	86.4		
	Thickness per Coat / mm	As Required		
	Functional Cure Time /Hours	16		
Recoat Time /Hours	4			
Mixed Viscosity /cps (where applicable)	Putty			
Chemical Resistance	7 days room temperature cure (30 days) - Testing carried out 30 days immersion at 21°C			
	Ammonia	Very Good	Methylene Chloride	Very Good
	Cutting Oil	Very Good	Sodium Hypochlorite 5% (Bleach)	Very Good
	Isopropyl Alcohol	Poor	Sodium Hydroxide 10%	Very Good
	Gasoline (Unleaded)	Very Good	Sulphuric Acid 10%	Very Good
	Hydrochloric Acid 10%	Very Good	Xylene	Fair
	Methyl ethyl Ketone (MEK)	Poor		
	Excellent = +/- 1% weight change			
	Very Good = +/- 1-10% weight change			
	Fair = +/- 10-20% weight change			
Poor = > 20% weight change				

Plastic Steel Putty (A)

APPLICATION INFORMATION

Cure	A 12.7mm thick section of Devcon Plastic Steel Putty will harden at 21°C in 4 hours. The material will be fully cured in 16 hours at which time the material can be machined, drilled or painted. The actual cure time of epoxy is determined by the mass used and the room temperature at time of repair.
Surface Preparation	<p>Proper surface preparation is essential to a successful application. The following procedures should be considered:</p> <ul style="list-style-type: none"> • All surfaces must be dry, clean and rough. • If surface is oily or greasy use Devcon Fast Cleaner 2000 Spray/Cleaner Blend 300 to degrease the surface. • Remove all paint, rust and grime from the surface by abrasive blasting or other mechanical techniques. • Aluminum repairs: Oxidation of aluminum surfaces will reduce the adhesion of an epoxy to a surface. This film must be removed before repairing the surface, by mechanical means such as grit-blasting or chemical means. • Provide a "profile" on the metal surface by roughening the surface. This should be done ideally by grit blasting (8-40 mesh grit), or by grinding with a coarse wheel or abrasive disc pad. An abrasive disc may be used provided white metal is revealed. Do not 'feather edge' epoxy materials. Epoxy material must be 'locked in' by defined edges and a good 3 - 5 mil profile. • Metal that has been handling sea water or other salt solutions should be grit blasted and high pressure water blasted and left overnight to allow any salts in the metal to 'sweat' to the surface. Repeat blasting may be required to 'sweat out' all the soluble salts. A test for chloride contamination should be performed prior to any epoxy application. The maximum soluble salts left on the substrate should be no more than 40 p.p.m. (parts per million). • Chemical cleaning with Devcon Fast Cleaner 2000 Spray/Cleaner Blend 300 should follow all abrasive preparation. This will help to remove all traces of sandblasting, grit, oil, grease, dust or other foreign substances. • Under cold working conditions, heating the repair area to 38°C - 43° C immediately before applying any of Devcon's Metal-filled Epoxies is recommended. This procedure dries off any moisture, contamination or solvents and assists the epoxy in achieving maximum adhesion to the substrate. • Always try to make the repair as soon as possible after cleaning the substrate, to avoid oxidation or flash rusting. If this is not practical, a general application of FL-10 Primer will keep metal surfaces from flash rusting.
Mixing	Plastic Steel Putty (A) is formulated to be a dense mix that can be applied easily to overhead and vertical surfaces without running or sagging. Add the hardener to resin and mix thoroughly on a mixing board using a spatula. Do not mix in the containers.
Application	For best results, product should be kept and applied at room temperature. Plastic Steel Putty (A) can be applied when temperatures are between 13°C and 52°C. Spread the putty over prepared surface with a putty knife. Press firmly to ensure maximum surface contact and avoid trapping air. To bridge large gaps or holes use fibreglass, sheet metal or wire mesh.
Shelf life & Storage	A shelf life of 3 years from date of manufacture can be expected when stored at room temperature (22°C) in their original containers
Precaution	For complete safety and handling information, please refer to Material Safety Data Sheets (MSDS) prior to using this product.

Plastic Steel Putty (A)

Warranty

ITW Devcon will replace any material found to be defective. As the storage, handling and application of this material is beyond our control we can accept no liability for the results obtained.

Disclaimer

All information on this data sheet is based on laboratory testing and is not intended for design purposes. ITW Devcon makes no representations or warranties of any kind concerning this data.

For product information visit www.devconeurope.com alternatively for technical assistance please call +44 (0) 870 458 7388 (UK) or +49 431 718830 (Germany).