



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex[®] Gasket Remover

INDUSTRIAL

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex[®] Gasket Remover is an aerosol product designed to remove gaskets and gasket residue from any type of metal housing. The product will also remove chemical formed-in-place gaskets.

PRODUCT BENEFITS

- Penetrates and cleans intricate shapes
- Will not run, even on vertical surfaces
- Eliminates excessive scraping and potential damage to flanged surfaces
- Saves time and labor

TYPICAL APPLICATIONS

- Removes baked-on gaskets and gasket cements
- Removes formed-in-place gaskets
- Removes gaskets from aluminum without scraping
- Removes gaskets from small, difficult to reach areas

DIRECTIONS FOR USE

1. Provide adequate ventilation.
2. Protect painted and non-metal surfaces from overspray. The product will remove paint.
3. Shake can well. Note: The product does not require a ball agitator. For best results, the aerosol can should be at room temperature before spraying.
4. Holding can 8 to 10 inches from the surface to be cleaned, press the nozzle and spray the product onto the old gasket.
5. Allow to set 5 to 10 minutes. Remove dissolved gasket with a putty knife. Repeat if required.

For Cleanup

1. Turn can upside-down and spray to clear nozzle.
2. Clean hands with Permatex[®] brand hand cleaners.

PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Methylene chloride
Appearance	Clear liquid
Odor	Solvent
Flash Point	Aerosol, contents under pressure, consult MSDS
NFPA 704 Flammability Rating	4 (Highly Flammable)

This product is not recommended for use in pure oxygen and/or oxygen rich systems.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
80646 (4MA)	16 oz. aerosol can

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8_ to 28_C (46_ to 82_F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

GENERAL INFORMATION

NOT FOR PRODUCT SPECIFICATIONS.
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87PERMATEX) 09/02